



DIMENSION	1/2"	1/2"	3/4"	3/4"	1"	1"
	Class 150	Class 300	Class 150	Class 300	Class 150	Class 300
A (SR)	8-5/8"	9"	9-7/8"	10-1/4"	10-3/8"	10-5/8"
A (DA)	8-5/8"	9"	9-1/8"	9-1/2"	9-3/4"	10"
B (SR)	7-3/4"	7-3/4"	8-1/8"	8-1/8"	8-1/8"	8-1/8"
B (DA)	5-3/4"	5-3/4"	5-3/4"	5-3/4"	5-3/4"	5-3/4"
C (SR)	4-1/2"	4-1/2"	5-1/4"	5-1/4"	5-1/2"	5-1/2"
C (DA)	4-1/2"	4-1/2"	4-7/8"	4-7/8"	5-1/4"	5-1/4"
D	1-3/4"	1-7/8"	1-7/8"	2-3/8"	2-1/8"	2-7/16"
E	3-1/2"	3-3/4"	3-7/8"	4-5/8"	4-1/4"	4-7/8"
F (SR)	1-5/16"	1-5/16"	1-3/4"	1-3/4"	1-3/4"	1-3/4"
F (DA)	1-5/16"	1-5/16"	1-5/16"	1-5/16"	1-5/16"	1-5/16"
G (SR)	1-7/8"	1-7/8"	2"	2"	2"	2"
G (DA)	1-7/8"	1-7/8"	1-7/8"	1-7/8"	1-7/8"	1-7/8"
H (SR)	3-1/4"	3-1/4"	3-3/8"	3-3/8"	3-3/8"	3-3/8"
H (DA)	3-1/4"	3-1/4"	3-1/4"	3-1/4"	3-1/4"	3-1/4"
J (SR)	2-5/8"	2-5/8"	3-1/2"	3-1/2"	3-1/2"	3-1/2"
J (DA)	2-5/8"	2-5/8"	2-5/8"	2-5/8"	2-5/8"	2-5/8"
K	4-1/4"	5-1/2"	4-5/8"	6"	5"	6-1/2"
NOTE 1: "H" IS CENTERLINE TO OUTSIDE SURFACE OF SOLENOID- ADD 1-1/8" IF EQUIPPED WITH QUADRANT BREATHER BLOCK						
NOTE 2: ADD 3-1/8" TO "A" & "C" DIMENSIONS IF A DGO IS MOUNTED BETWEEN VALVE & C-SERIES ACTUATOR.						



Series F1-CS/SS with C-Series Pneumatic Actuator