

**C-SERIES ACTUATOR TO M2-CS/SS SERIES MOUNTING CHART-Revised 6-04**

M2-CS & SS REDUCED PORT SIZE	M2-CS & SS FULL PORT SIZE	MAX BREAK	C-MAX UNIT	BRACKET NUMBER	BOLTING HARDWARE	DRIVE INSERT REQUIRED	DRIVER NUMBER
1/2"	1/4" & 3/8"	100 IN-LB	C-250(DA & SR)	B-4	(4) M6 x 1.0P x 12MM w/Lockwashers PLUS (4) 1/4"-20UNCx1/2" w/Lockwashers	NONE	D-10A
3/4"	1/2"	200 IN-LB	C-250(DA)	B-4	(4) M6 x 1.0P x 12MM w/Lockwashers	NONE	D-10A
3/4"	1/2"	200 IN-LB	C-450SR	B-4	PLUS (4) 1/4"-20UNCx1/2" w/Lockwashers	14M11	D-10A
1"	3/4"	230 IN-LB	C-250 (DA)	B-5	(4) M6 x 1.0P x 12MM w/Lockwashers	NONE	D-11A
1"	3/4"	230 IN-LB	C-450SR	B-5	PLUS (4) 1/4"-20UNCx1/2" w/Lockwashers	14M11	D-11A
1-1/4"	1"	250 IN-LB	C-450(DA & SR)	B-5	(4) M6 x 1.0P x 12MM w/Lockwashers PLUS (4) 1/4"-20UNCx1/2" w/Lockwashers	NONE	D-25A
1-1/2"	1-1/4"	380 IN-LB	C-450(DA)	B-6	(4) M6 x 1.0P x 12MM w/Lockwashers	NONE	D-17A
1-1/2"	1-1/4"	380 IN-LB	C-1000SR	B-6	PLUS (4) 1/4"-20UNCx1/2" w/Lockwashers	17M14	D-17A
2"	1-1/2"	520 IN-LB	C-1000(DA & SR)	B-6	(4) M6 x 1.0P x 12MM w/Lockwashers PLUS (4) 1/4"-20UNCx1/2" w/Lockwashers	17M14	D-17A
2-1/2" (RTFE)	2" (RTFE)	660 IN-LB	C-1000(DA)	B-7	(4) M8X 1.25P x 15MM w/Lockwashers	NONE	D-26A
2-1/2" (RTFE)	2" (RTFE)	660 IN-LB	C-2250SR	B-7	PLUS (4) 5/16"-18UNC x 1/2" w/Lockwashers	22M17	D-26A
2-1/2" (PEEK)	2" (PEEK)	950 IN-LB	C-1000(DA)	B-7	(4) M8X 1.25P x 15MM w/Lockwashers	NONE	D-26A
2-1/2" (PEEK)	2" (PEEK)	950 IN-LB	C-2250SR	B-7	PLUS (4) 5/16"-18UNC x 1/2" w/Lockwashers	22M17	D-26A