

ROV Camera.

ROV Tools.



DESCRIPTION

The ROV camera is used for inspection of difficult locations. The camera is mounted in plastic outer casing to prevent damage to seal hubs. A colour camera with local ring LED light source is mounted in a plastic housing with a fish tail style handle for manipulation by the ROV. The camera is supplied with three joints and two lengths of camera tube to suit the specific application.

FEATURES

- ROV operated Inspection Camera.
- Supplied with range of configurations.
- Fish Tail Handle.
- Supplied in offshore suitable transit case.

ROV Camera.

ROV Tools.

SPECIFICATIONS

Horizontal Resolution	470 TV Lines – PAL
Scanning	625 Line/0 Hz –PAL
Video Output	Composite, 1.0V peak to peak into 75 ohm
Focus Control	Fixed, 75mm to infinity
Field of view in water	54 Deg Diagonal.
Power Input :	11-30VDC, 310 mA (max)
Electrical Connector	Sea-Conn BH-4-MP
Depth Rating	4,000m
Cable	4m Sea-Conn connecting cable
Camera Material	Titanium Body

PART NUMBERS & OPTIONS

A198-017-001/02	ROV Camera.
A198-017-010	Spares Kit

WHAT'S IN THE BOX

Camera in mounting
ROV Handle
3m Cable
Extension tube

